

Material Data Sheet

ESD-PETG

**MATERIAL
4PRINT**

your filament experts



Layer adhesion



Weather resistance



Easy to print




Heat resistance



Tensile strength



Impact resistance



Description

ESD-PETG is an electrically conductive or antistatic filament. Our ESD filament was developed to protect electronic components that are sensitive to electrostatic discharge.

Identification

Name	ESD-PETG
Chemical Name	Polyethylenterephthalat + Glykol
Usage	FDM 3D Printing
Manufacturer	Material 4 Print GmbH & Co. KG, Germany

Properties

Test	Value	Method
Specific Gravity	1,27 g/cm ³	ASTM D792
Elongation at Break	70%	ASTM D638
Tensile Strength	53 MPa	ASTM D638
Flexural Modulus	2150 MPa	ASTM D790
Melting Point	200 - 230 °C	ASTM D3418
Heat Distortion Temperature	70 °C	ASTM D648
Flammability	HB	UL-94
Surface Resistance	>10 ⁶ - 10 ⁸ <	ASTM D257

If you have any further questions about the product or problems in its use, please contact info@material4print.de



Certificate



Certification depends on colors in the final product. More info in the additional information sheet.

Storage

Store at room temperature, out of direct heat and sunlight and in a dry place.

Print Settings

Nozzle Temperature: 235-260 °C
Bed Temperature: 60-80 °C

These data were taken from the raw material manufacturer.

12.04.2021

www.material4print.de

Contact: info@material4print.de